

Oil resistant agent RF-7610

Features and advantages:

RF-7610 is a levelling oil resistant agent suitable for solvent-based coatings with good high temperature resistance

- 1. When the substrate is contaminated by silicone oil and grease, it will cause the coating problem (such as poor adhesion, pinholes, craters, etc.), which can effectively solve the coating problem.
- 2. With excellent leveling, smoothing and release characteristics, it can be used in heat resistant non-stick kitchen paint formula, heat resistant temperature up to 250° C.
- 3. Fabric processing applications, soft. Water and smooth effect, increase the durability of washable.
- 4. Poor recoating

Physicochemical property:

appearance	Clear to a turbid liquid
Nonvolatile fraction	≥98%
Specific gravity	About 0.964
chroma	≤40
viscosity	50-125CP
Acid number	≤0.5
Make up	Modified polysiloxane

Product application: solvent-based coating solvent-based ink

Usage: Please test the optimal amount before use; Stir well and use

Addition amount: Add 0.05%-0.30% to the full amount



Storage conditions: Keep away from heat and fire, in a cool and ventilated place, keep the container close, and the storage environment is 0° C to 40° C.

Packing: Net weight: 200kg/25kg

Validity: RF-7610 from the date of production, the warranty period is 24

months