



Antifoaming agent for adhesive

RP-6405

Features and advantages:

RP-6405 is a mixture of polyether, mineral oil, and nonionic surfactants for foam control in coatings, emulsion polymerization, white latex, and adhesives with long-lasting results.

- It has excellent continuous anti-bubble effect and has very good compatibility.
- Strong versatility, can produce beautiful film.
- Strong combination, not easy to shrink oil, no adverse effect on the color of the paint.

Product Specifications:

appearance	Translucent colorless - light yellow viscous phase liquid
Active ingredient	100%
Specific gravity	0.89 g/ml
Ionic type	nonionic
Water solubility	Disperse in water, easily emulsified

Application fields: acrylic emulsion, white latex, pressure sensitive adhesive and other industries.

Usage and dosage: can be added to the system in the form of the original,

Tianjin Ruike Chemical Co. LTD

Tel:+86 18526852692

Add:Room 116-11, 160 Xiangyuan Road, Jingjin Science and Technology Valley Industrial Park, Wuqing District, Tianjin

tjrkhg@126.com

www.rk-chem.com



the recommended dosage of 0.1-0.5%. It can be added directly or diluted. Stir well or shake well before use. (The stratification in the storage process does not affect the use efficiency) below 5°C will be solidified or stratified, before use below 5°C, please use a warm bath to 30-40°C and fully mixed, does not affect the use efficiency.

Packing: 25kg, 180kg plastic drum packing.

Storage and precautions: no frost, below 40°C, 12 months