



---

---

## Thick paste type defoamer

### RP-6411

#### Features and advantages:

RP-6411 is a silicone thick paste type defoamer, suitable for elastic coating systems and adhesives, and the effect is long-lasting.

- It has excellent continuous anti-bubble effect, and is suitable for all kinds of high viscosity elastic brushed coatings and all kinds of thick paste coatings.
- It has good defoaming effect on the remaining microbubbles and makes the painting more beautiful.
- It has little effect on gloss and is more suitable for one-time coating of elastic coatings.

#### Product Specifications:

appearance	Yellowish brown viscous liquid
Active ingredient	100%
Specific gravity	0.86 g/ml
Ionic type	nonionic
Water solubility	Insoluble in water

**Application fields:** ordinary interior and exterior paint, high grade putty, flat coating elastic and thick paste elastic paint. Water-based

Tianjin Ruike Chemical Co. LTD

Tel:+86 18526852692

Add:Room 116-11, 160 Xiangyuan Road, Jingjin Science and Technology Valley Industrial Park, Wuqing District, Tianjin

[tjrkhg@126.com](mailto:tjrkhg@126.com)

[www.rk-chem.com](http://www.rk-chem.com)



ink, water-based binder.

**Usage and dosage:** The recommended addition amount is 0.1-1.2% of paint quality.

Add 30-50% of the mass in the grinding stage and the remaining 70-50% in the paint mixing stage (before adding the hole liquid).

For long-term storage, shake evenly before use, without affecting the use efficiency.

Thick paste type elastic building latex paint	High grade building putty
The recommended dosage is 0.2-0.8% of the total formula	The recommended dosage is 0.1-0.5% of the total formula
Flat elastic architectural latex paint	Water-based ink
The recommended dosage is 0.1-0.2% of the total formula	The recommended dosage is 0.1-0.5% of the total formula

**Packing:** 16 kg iron drum, 25 kg, 180 kg plastic drum packing.

**Storage and precautions:** no frost, below 40°C, 12 months