

Silicone wetting agent

RK-8212

Features and advantages:

RK-8212 is a cost-effective silicone wetting agent, with ultra-low surface tension, does not improve smoothness, does not affect the adhesion fastness and recoating, a wide range of applications.

(1) Ultra-low surface tension (0.1% aqueous solution, static surface tension as low as 20.5mN/m)

(2) Excellent substrate wettability and permeability, effectively prevent shrinkage cavity

(3) Excellent resin miscibility

(4) does not improve smoothness, does not affect the adhesion fastness and recoating between layers

Product specifications:



appearance	Transparent liquid	
Valid copy of	100%	1
Chemical composition	Organosiloxane copolymer	

Application scope:

(1) • Water-based paint, ink Recommended dosage: 0.1-1.0% for the total formula in the form of supply (2) water fountain solution Recommended dosage: 1.5-2.0% for the total formula in the form of supply (3) water-based wood primer and water-based plastic paint Recommended dosage: 0.2-0.3% of the total formula in supply form (4) water-based leather coating or leather tanning Recommended dosage: 0.3-0.5% of the total formula in the form of supply (5) Metal paint Recommended dosage: 0.3-0.5% of the total formula in the form of supply (6) Petroleum extraction, cleaning and washing products **Recommended dosage:** 0.6-1.0% of the total formula in the form of supply Usage: pre-diluted or directly added to the coating in the form of supply. Packing: 25kg, plastic drum / 200kg, iron drum. Storage: Store in unopened original packaging for 12 months