

Surfactant

RK-8319

Product features and advantages:

RK-8319 is used in water-based and oil-based coating wetting formulation systems. Good miscibility in each coating system, soluble in water, with excellent wetting and leveling effect, good recoating property, high temperature resistance; Especially suitable for automotive paint wetting agent, industrial paint wetting agent, plastic paint wetting agent, wood furniture paint wetting agent, building paint substrate wetting agent, inkjet ink wetting agent, all kinds of film wetting agent, glass substrate wetting agent.

1. Water and oil are universal and soluble in water
2. Super wetting ability, anti-shrinkage hole
3. Good recoating
4. High temperature resistance, excellent adhesion

Technical index:

appearance	Transparent liquid
Active substance content	100%
Chemical composition	Organosiloxane copolymer

Collar field should be used

Automotive paint, industrial paint, plastic, wood and furniture paint

Recommended addition

Total formula in the form of supply: 0.1-1.0%

Architectural Coatings

Recommended addition

Total formula in the form of supply: 0.1-1.0%

Decorative paint, inkjet ink

Recommended addition

In the form of supply, 0.2-1.0% of the total formula

○ All kinds of film material, glass substrate

In the form of supply, 0.2-1.0% of the total formula

Usage: Pre-dilution or directly added to the paint according to the supply form can be, low temperature may cause turbidity, after heating to eliminate, do not affect the use.

Packing: Net weight: 200kg/25kg

Storage strips: Stored in unopened original packaging and used within 12 months from the date of production.